

TELELINE

Light-emitting diode module

Teleline T2 2,0W

FOR LIGHT BOXES

DESIGNED FOR BACKLIGHT LIGHTBOXES

DEPTH 70-100 MM

BEST FOR 70-100MM DEEP LIGHTBOXES

1:3 RATIO

RECOMMENDED DEPTH: C-C DISTANCE RATIO

2 W

HIGH POWER FOR EXTRA BRIGHTNESS

IP 67

DUST AND WATER PROTECTED

200 lm

HIGH BRIGHTNESS 200 LM PER MODULE

6500 K

6500 K AND OTHER COLORS

5 YEARS WARRANTY

5 YEAR EXTENDED WARRANTY

TECHNICAL INFORMATION


LED type	3030
Input	12V DC
Color temperature	6500K
Beam angle	175°
Protection level	IP67
Center-to-center distance	350 mm
Working temperature	-30°C + 50°C
Available colors	●
Power	2 W
Light output	200 lm

ILLUMINATION TABLE

Installation depth	Distance between centers	Quantity per 1 sq.m.	Power per 1 sq.m.
70 mm	180 mm	36 pcs	43,2 W
80 mm	200 mm	25 pcs	30 W
90 mm	230 mm	25 pcs	30 W
100 mm	250 mm	16 pcs	19,2 W




LIGHT DISTRIBUTION GRAPH
Beam angle is 175°



DIMENSIONS



CONNECTION



PACKAGING

Packing type	Chain	Package	Box
Quantity	20 pcs	100 pcs	1600 pcs
Weight	0,3 kg	1,5 kg	25,2 kg